

Membrane injection system

for buildings without a basement



2LINE MIS25 1x6-13 PRO

gabocom Artikel-Nr.: 43845



- **Controlled RESINATOR resin discharge thanks to proven membrane injection system**
- **Tool-free assembly with RESINATOR double syringe**
- **Horizontal or inclined installation up to 45° inclination**



For reliable sealing of fibre optic cables.

Picture may differ from selected product

FACTS

Advantages:

- Sealing in all common wall types (DIN 18533/WU concrete)
- Minimum RESINATOR resin quantity thanks to adhesive collar
- Small opening diameter Øi 25 mm
- Quick to assemble in just a few minutes

Scope of delivery:

- 1 piece of 2LINE MIS25
- 1 piece of RESINATOR dual syringe, 25 ml
- 1 piece of wall terminator element

Dimensions:

- Area of application: 1 fibre-optic cable with Øa 6 - 13 mm
- for drill holes Øi: 25 mm
- for wall thicknesses starting from 150 mm

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2
- 1 fibre-optic cable with Øa 6 - 13 mm

Material:

- Membrane sleeve: TPE
- Foil flange: Aluminium-plastic composite foil with butyl rubber
- Wall terminator element: PCFR

Tightness:

- gastight and watertight to 1.0 bar

DIN:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

FEATURES

Number of cables/medium:	1
Suitable for medium pipe OD (mm):	6-13 MM

PICTURES

